

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen

2012

Nebraska Summary: S841 Massey Ferguson 7624

Nebraska Tractor Test Laboratory

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>

 Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Laboratory, Nebraska Tractor Test, "Nebraska Summary: S841 Massey Ferguson 7624" (2012). *Nebraska Tractor Tests*. 3098.

<https://digitalcommons.unl.edu/tractormuseumlit/3098>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

SUMMARY OF OECD TEST 2706—NEBRASKA SUMMARY 841

MASSEY FERGUSON 7624 DYNA VT DIESEL

CONTINUOUSLY VARIABLE TRANSMISSION

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Diesel Consumption Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	D.E.F. Consumption Gal/hr (l/h)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION						
Rated Engine Speed—(PTO speed—1031 rpm)						
187.5 (139.8)	2098	10.86 (41.10)	0.404 (0.246)	17.26 (3.40)	0.59 (2.23)	
Standard Power Take-off Speed (1000 rpm)						
201.2 (150.0)	2034	11.16 (42.25)	0.387 (0.236)	18.03 (3.55)	0.68 (2.56)	
Maximum Power (1 hour)						
212.0 (158.1)	1950	11.55 (43.72)	0.380 (0.231)	18.36 (3.62)	0.73 (2.77)	
VARYING POWER AND FUEL CONSUMPTION						
187.5 (139.8)	2098	10.86 (41.10)	0.404 (0.246)	17.26 (3.40)	0.59 (2.23)	Air temperature
160.4 (119.6)	2119	9.39 (35.55)	0.408 (0.249)	17.08 (3.36)	0.52 (1.96)	72°F (22°C)
120.5 (89.9)	2131	7.64 (28.93)	0.442 (0.269)	15.77 (3.11)	0.43 (1.61)	Relative humidity
80.3 (59.9)	2139	5.71 (21.63)	0.496 (0.302)	14.06 (2.77)	0.28 (1.06)	64%
40.6 (30.3)	2149	3.97 (15.01)	0.682 (0.415)	10.23 (2.02)	0.20 (0.75)	Barometer
---	2153	2.37 (8.97)	---	---	---	30.3" Hg (102.5 kPa)
Maximum torque - 723 lb.-ft. (980 Nm) at 1451 rpm Maximum torque rise - 54.0% Torque rise at 1700 engine rpm - 40% Power increase at 1950 engine rpm - 13%						

DRAWBAR PERFORMANCE

(Unballasted - Front Drive Engaged)

FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp.°F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—Turtle 8									
158.5 (118.2)	12115 (53.9)	4.91 (7.89)	2093	6.1	0.438 (0.266)	15.89 (3.13)	183 (84)	46 (8)	30.4 (103.0)
75% of Pull at Maximum Power—Turtle 8									
118.5 (88.4)	9105 (40.5)	4.88 (7.86)	2111	5.0	0.481 (0.292)	14.48 (2.85)	181 (83)	46 (8)	30.4 (103.0)
50% of Pull at Maximum Power—Turtle 8									
79.8 (59.5)	6025 (26.8)	4.97 (7.99)	2129	4.1	0.547 (0.333)	12.72 (2.51)	181 (83)	46 (8)	30.4 (103.0)
75% of Pull at Reduced Engine Speed—Turtle 10									
118.1 (88.1)	9105 (40.5)	4.87 (7.83)	1390	4.9	0.402 (0.244)	17.32 (3.41)	181 (83)	48 (9)	30.1 (102.0)
50% of Pull at Reduced Engine Speed—Turtle 10									
79.7 (59.4)	6045 (26.9)	4.94 (7.95)	1405	4.2	0.431 (0.262)	16.14 (3.18)	176 (80)	48 (9)	30.1 (102.0)

Location of tests: Centre d'Antony, 1 rue Pierre-Giles de Gennes, CS 10030 92761 Antony, Cedex France

Dates of tests: January - May, 2012

Manufacturer: AGCO S.A. ZA, n2, BP 60307, Avenue Blaise Pascal, 60026 Beauvais, Cedex, France

FUEL and OIL: Fuel No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.838 **Fuel weight** 6.98 lbs/gal (0.836 kg/l) **Diesel Exhaust Fluid (DEF)** 32% aqueous urea solution **DEF weight** 9.08 lbs/gal (1.091 kg/l) **Oil SAE** 15W40 **API service classification** CH4 **Transmission and hydraulic lubricant** BP Terrac Tractan 910W/40 **Front axle lubricant** SAE 85W140 API GL-5

ENGINE: Make Sisu Diesel **Type** six cylinder vertical with turbocharger, air to air intercooler and SCR (selective catalyst reduction) technology **Serial No.** W00450 **Crankshaft** lengthwise **Rated engine speed** 2100 **Bore and stroke** 4.252" x 5.276" (108.0 mm x 134.0 mm) **Compression ratio** 17.8 to 1 **Displacement** 449 cu in (7365 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner** two paper elements **Oil filter** one full flow cartridge **Oil cooler** engine coolant heat exchanger for crankcase oil, radiator for hydraulic and transmission oil **Fuel filter** one paper element **Muffler** underhood **Exhaust** vertical **Cooling medium temperature control** thermostat and variable speed fan

CHASSIS: **Type** front wheel assist **Serial No.** T318901 **Tread width** rear 52.8" (1340 mm) to 87.8" (2230 mm) front 52.8" (1340 mm) to 87.8" (2230 mm) **Wheelbase** 117.8" (2993 mm) **Hydraulic control system** direct engine drive **Transmission** CVT. A combination of mechanical and hydrostatic sections allow an infinite speed adjustment within the ranges noted. The transmission has two mechanical ranges. **Nominal travel speeds mph (km/h)** forward: Low range 0-19 (0-30), high range 0-25 (0-40) reverse: Low range 0-11 (0-17), high range 0-19 (0-30) **Clutch** a foot pedal controls the hydrostatic oil flow **Brakes** multiple wet disc hydraulically operated by two foot pedals that can be locked together **Steering** hydrostatic **Power take-off** 540 rpm at 1932 engine rpm or 1000 rpm at 2035 engine rpm **Unladen tractor mass** 18695 lb (8480 kg)

DRAWBAR PERFORMANCE

(Unballasted - Front Drive Engaged) MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)	
120.2 (89.6)	16750 (74.5)	2.69 (4.33)	2128	14.4	Turtle 4.5 0.492 (0.299)	14.16 (2.79)	181 (83)	50 (10)	30.1 (102.0)
133.7 (99.7)	15850 (70.5)	3.16 (5.09)	2115	11.1	Turtle 5.5 0.488 (0.297)	14.26 (2.81)	183 (84)	45 (7)	30.4 (103.0)
159.7 (119.1)	15850 (70.5)	3.78 (6.08)	2035	10.0	Turtle 6.5 0.452 (0.275)	15.38 (3.03)	183 (84)	45 (7)	30.4 (103.0)
166.7 (124.3)	13240 (58.9)	4.72 (7.60)	2011	9.1	Turtle 8 0.431 (0.262)	16.14 (3.18)	183 (84)	46 (8)	30.4 (103.0)
167.9 (125.2)	11535 (51.3)	5.46 (8.79)	2002	7.5	Turtle 10 0.432 (0.263)	16.09 (3.17)	181 (83)	46 (8)	30.4 (103.0)
165.2 (123.2)	9915 (44.1)	6.25 (10.06)	2024	5.1	Turtle 11 0.436 (0.265)	15.95 (3.14)	185 (85)	49 (9)	30.1 (102.0)
163.5 (121.9)	7945 (35.3)	7.72 (12.43)	2015	4.3	Turtle 13 0.442 (0.268)	15.76 (3.10)	185 (85)	52 (11)	30.1 (102.0)
159.7 (119.1)	7035 (31.3)	8.51 (13.70)	1996	3.0	Turtle 15 0.451 (0.274)	15.43 (3.04)	187 (86)	54 (12)	30.1 (102.0)
151.0 (112.6)	11490 (51.1)	4.93 (7.93)	2035	7.4	Rabbit 8 0.474 (0.288)	14.68 (2.89)	181 (83)	41 (5)	30.1 (102.0)
155.7 (116.1)	10545 (46.9)	5.54 (8.91)	2019	5.8	Rabbit 9 0.464 (0.282)	14.98 (2.95)	183 (84)	41 (5)	30.1 (102.0)
156.8 (116.9)	9350 (41.6)	6.29 (10.12)	2011	5.1	Rabbit 10 0.461 (0.280)	15.10 (2.97)	181 (83)	41 (5)	30.1 (102.0)
162.9 (121.5)	8095 (36.0)	7.55 (12.15)	2025	4.0	Rabbit 12 0.445 (0.271)	15.63 (3.08)	183 (84)	43 (6)	30.1 (102.0)
164.4 (122.6)	7015 (31.2)	8.79 (14.05)	2007	3.3	Rabbit 14 0.439 (0.267)	15.84 (3.12)	185 (85)	43 (6)	30.1 (102.0)
159.6 (119.0)	6025 (26.8)	9.93 (15.99)	2035	3.0	Rabbit 16 0.451 (0.274)	15.43 (3.04)	185 (85)	45 (7)	30.1 (102.0)

REPAIRS AND ADJUSTMENTS: No repairs or adjustments.

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's claim of 15% power bulge. The manufacturer's claim of 39 GPM (150 lpm) remote hydraulic flow, with optional pump was not verified. The performance figures on this summary were taken from a test conducted under the OECD Code 2 test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2706**, Nebraska Summary 841, January 30, 2013.

Roger M. Hoy
Director

M.R. Riley
P.J. Jasa
J.D. Luck
Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	Front wheel drive	
	Engaged dB(A)	Disengaged dB(A)
At no load in Turtle 8	70.0	70.0
Bystander		--

TIRES, BALLAST AND WEIGHT

Rear Tires - No., size, ply & psi(kPa)

Front Tires - No., size, ply & psi(kPa)

Height of Drawbar

Static Weight with operator - Rear

- Front

- Total

Tested without ballast

Two 460/85R38;**,14(100)

Two 480/70R30;**,14(100)

21.7 in (550 mm)

10725 lb (4865 kg)

8135 lb (3690 kg)

18860 lb (8555 kg)

HYDRAULIC PERFORMANCE

CATEGORY: III

Quick Attach: None

OECD Static test

Maximum force exerted through whole range: 13715 lbs (61.0 kN)

i) Sustained pressure of the open relief valve: 2890 psi (199 bar)

two outlet sets combined

ii) Pump delivery rate at minimum pressure: 30.0 GPM (113.4 l/min)

iii) Pump delivery rate at maximum

hydraulic power: 26.9 GPM (101.9 l/min)

Delivery pressure: 2305 psi (159 bar)

Power: 36.2 HP (27.0 kW)

one outlet set

ii) Pump delivery rate at minimum pressure: 29.6 GPM (112.2 l/min)

iii) Pump delivery rate at maximum

hydraulic power: 27.2 GPM (103.0 l/min)

Delivery pressure: 1945 psi (134 bar)

Power: 30.9 HP (23.1 kW)

HITCH DIMENSIONS AS TESTED—NO LOAD

	inch	mm
A	31.9	810
B	14.0	355
C	14.4	365
D	12.0	305
E	8.8	223
F	10.9	276
G	36.4	925
H	2.4	60
I	16.4	416
J	25.5	649
K	26.2	665
L	47.6	1209
M	26.9	684
N	40.6	1030
O	8.5	216
P	49.6	1259
Q	39.7	1008
R	31.1	790

